

# MASTER FORCED AIR HEATER (B1)



SKU: PIN B150

**Heating Area 400 m<sup>2</sup>**  
**44 L Fuel Tank**  
**Fuel Consumption 4.2 L/hr**

**PROFESSIONAL HEATING SOLUTIONS BACKED BY  
EUROPEAN ENGINEERING.**

**MASTER forced air diesel heaters deliver dependable, high-capacity heating for commercial, industrial, and agricultural environments.**

- Powerful heat output ranging from 20 kW to over 44 kW
- Rugged construction with stainless steel combustion chambers for long service life
- Integrated safety features including flame detection and overheat protection
- Easy maintenance access and portable designs with built-in wheels and handles (B100, B150)

## Features

- High air flow
- Two oil filters – oil tank filter and suction filter
- Thermally protected motor
- Electronic flame control with photocell
- Stainless steel combustion chamber
- Oil tank with level indicator
- Designed for easy handling and transportation
- Easy maintenance
- Made in Italy
- Suitable for:
  - Agriculture
  - Automotive
  - Buildings and commercial spaces
  - Construction
  - General industry and production
  - Military and aerospace
  - Rental companies

## Specifications

- **Units:** B 150



## Recommended Accessories

- **Digital Room Thermostat 10 m** PIS 4150.134
- **Digital Room Thermostat THD 5 m Cable** PIS 4150.133
- **MASTER Li-Ion Radiant Heater – 17 kW (58,000 BTU) Output** PIN DC61
- **MASTER Forced Air Heater (B1)** PIN B70
- **MASTER Forced Air Heater (B1)** PIN B100
- **MASTER Radiant Heater – 17 kW (58,000 BTU) Output** PIN XL61
- **Room Thermostat TH5 10 m Cable** PIS 4150.112
- **Room Thermostat TH5 3M** PIS 4150.109



# MASTER FORCED AIR HEATER (B1)



- **Heating Output:** 44 kW (150,000 BTU)
  - **Heating Area:** 400 m<sup>2</sup>
  - **Power:** 240 V 10 A
  - **Fuel Tank capacity:** 44 L
  - **Fuel Consumption:** 4.2 L/h
  - **Working Time:** 10.5 hr
  - **Air flow:** 900 m<sup>3</sup>/hr
  - **Electric power:** 0.28 kW
  - **Rated current:** 1.2 A
  - **Thermostat control:** Analogue or digital
  - **Fuel:** Diesel or Kerosene
  - **Protection:** IP41
  - **Product size (L x W x H):** 1,075 mm x 600 mm x 480 mm
  - **Box size (L x W x H):** 1,110 mm x 400 mm x 450 mm
  - **Net weight:** 25 kg
  - **Gross weight:** 28 kg
  - **Pallet:** 10 pcs
  - **Dual voltage:** Available
- 

