

HIGH PRESSURE TRIPLEX PUMP - TW SERIES - SOLID, 24 MM SHAFT - COMET



SKU: 210 TW11025S

42.5 L/min @ 2500 PSI
1450 RPM
18.5 HP, 20 KG



Features

- Brass Head
- Die-Cast Aluminum Alloy for Protection Against Corrosion
- Piston Guides are Heat Treated Stainless Steel
- Highly Efficient Stainless Steel Check Valves
- Solid Ceramic Plungers
- Brass Manifold: Forged for Maximum Strength and Longer Life up to 345 bar
- Solid Bronze Alloy Connection Rods
- High Quality Tapered Roller Bearings
- Large Oil Capacity Dissipates Heat and Improves Lubrication for Longer Life
- High Volume up to 53,5 l/min
- Long Life Seals
- Exclusive No-Oil-Leak System in the crankcase minimising wear of the piston oil seal (Patented)
- Exclusive Sealing System Between Crankcase And Pump Head that prevents dust and dirt getting inside where the pistons work but letting water out (Patented)
- Solid Shaft 24 or 30 mm for Belt Drive, Gearbox or Flex Couplers
- Standard versions with p.t.o on right hand side, left side on request.



Specifications

- **Comet Model:** 6513 1200
- **Shaft:** Solid, 24 mm
- **Speed:** 1450 RPM
- **Flow:** 42.5 L/min - 11 GPM
- **Pressure:** 2500 PSI - 172 BAR - 17.2 Mpa
- **Power:** 18.5 HP - 13.7 kW
- **Weight:** 20 KG - 44 lbs
- **Inlet:** 3/4" BSP F
- **Outlet:** 1/2" BSP F



HIGH PRESSURE TRIPLEX PUMP - TW SERIES - SOLID, 24 MM SHAFT - COMET



- **Head Material:** Brass
 - **Pump Type:** Triplex
-

