

SKU: 222 HTXS1813S

**Flow 13.2 L/min**

**Pressure 2,500 PSI**

**Speed 1,450 RPM**

## Features

- Features patented "high tech" packings:
  - dynamic low-pressure seal retainer
  - superior low-pressure seal
  - innovative intermediate ring
  - superior high-pressure seal
- Ceramic plungers
- Patent-pending inlet/outlet valve cage
- Nickel-plated inlet/outlet valve plugs
- Nickel-plated forged brass manifold with an exclusive lifetime warranty
- Specifically designed to handle rigorous duty cycles, high temperatures and chemicals
- Ideal for use in carpet cleaning and other high pressure cleaning applications

## Specifications

- **Maximum Volume:** 3.5 GPM
- **Maximum Pressure:** 2,500 PSI
- **Maximum Speed:** 1,450 RPM
- **Maximum Inlet Pressure:** 125 PSI
- **Minimum Outlet Pressure:** 3 ft. water (2.6 in. Hg)
- **Maximum Fluid Temperature:** 185°F
- **Bore (in / mm):** .709 in. / 18 mm
- **Stroke (in / mm):** .394 in. / 10 mm
- **Oil Capacity:** 14.0 oz.
- **Inlet Port Thread:** 1/2"-14 BSP-F
- **Discharge Port Thread:** 3/8"-19 BSP-F
- **Shaft Diameter:** .945 in. / 24 mm
- **Weight:** 18 lbs.
- **Dimensions - Nominal:** 8.4" x 8.3" x 5.6"

