

HIGH PRESSURE TRIPLEX PUMP - RWS SERIES - SOLID, 24 MM SHAFT - COMET



SKU: 210 RWS5535S

21.4 L/min @ 3500 PSI
1750 RPM
13.1 HP, 11.2 KG



Features

- Brass Head
- Crankcase: Die-Cast Aluminum Alloy for Protection Against Corrosion
- Piston Guides are Heat Treated Stainless Steel
- Highly Efficient Stainless Steel Check Valves
- Solid Ceramic Plungers
- Brass Manifold: Forged for Maximum Strength and Longer Life up to 310 bar
- One Piece, Solid Bronze Alloy Connection Rods
- High Quality Tapered Roller Bearings
- Large Oil Capacity Dissipates Heat and Improves Lubrication for Longer Life
- Exclusive No-Oil-Leak System in the crankcase minimising wear of the piston oil seal (Patented)
- Exclusive Sealing System Between Crankcase And Pump Head that prevents dust and dirt getting inside where the pistons work but letting water out (Patented)
- Solid Shaft 24mm for Belt Drive, Gearbox or Flex Couplers
- Nickel plated head available on request
- Standard versions with p.t.o on right hand side, left side on request.



Specifications

- **Comet Model:** 6518 1500
- **Shaft:** Solid, 24 mm
- **Speed:** 1750 RPM
- **Flow:** 21.4 L/min - 5.7 GPM
- **Pressure:** 3500 PSI - 241 BAR - 24.1 Mpa
- **Power:** 13.1 HP - 9.6 kW
- **Weight:** 11.2 KG - 24.6 lbs
- **Inlet:** 1/2" BSP F



HIGH PRESSURE TRIPLEX PUMP - RWS SERIES - SOLID, 24 MM SHAFT - COMET



- **Outlet:** 3/8" BSP F
 - **Head Material:** Brass
 - **Pump Type:** Triplex
-

