

HIGH TEMPERATURE PRESSURE PUMP - TW SERIES - SOLID, 24 MM SHAFT - COMET



SKU: 210 TW7036S HT

26.6 L/min @ 3600 PSI
1450 RPM
16.5 HP, 20 KG



Features

- Hot Water Pump (max 85°C – 185°F)
- Brass Head
- Long Life Kevlar Seals
- Die-Cast Aluminum Alloy for Protection Against Corrosion
- Piston Guides are Heat Treated Stainless Steel
- Highly Efficient Stainless Steel Check Valves
- Solid Ceramic Plungers
- Brass Manifold: Forged for Maximum Strength and Longer Life up to 248 bar
- Solid Bronze Alloy Connection Rods
- High Quality Tapered Roller Bearings
- Large Oil Capacity Dissipates Heat and Improves Lubrication for Longer Life
- High Volume up to 42,5 l/min
- Exclusive No-Oil-Leak System in the crankcase minimising wear of the piston oil seal (Patented)
- Exclusive Sealing System Between Crankcase And Pump Head that prevents dust and dirt getting inside where the pistons work but letting water out (Patented)
- Solid Shaft 24 mm for Belt Drive, Gearbox or Flex Couplers
- Standard versions with p.t.o on right hand side, left side on request.

Specifications

- **Comet Model:** 6513 0704
- **Shaft:** Solid, 24 mm
- **Speed:** 1450 RPM
- **Flow:** 26.6 L/min - 7 GPM
- **Pressure:** 3600 PSI - 248 BAR - 24.8 Mpa
- **Power:** 16.5 HP - 12.4 kW



HIGH TEMPERATURE PRESSURE PUMP - TW SERIES - SOLID, 24 MM SHAFT - COMET



- **Weight:** 20 KG - 44 lbs
 - **Inlet:**
 - **Outlet:**
 - **Head Material:** Brass
 - **Pump Type:** High Temperature
-

