

HIGH TEMPERATURE PRESSURE PUMP - ZW SERIES - SOLID, 24 MM SHAFT - COMET



SKU: 210 ZW3530S HT

13 L/min @ 3000 PSI
1450 RPM
6.5 HP, 7.9 KG



Features

- Hot Water Pump (max 85°C – 185°F)
- Brass Head (Stainless Steel on request)
- Kevlar Seals
- Increased Fin Depth Increases Surface Area to Maximize Heat Dissipation
- Stainless Steel Unitized Check Valves
- Heat-Resistant Solid Ceramic Plungers Operating on Lubricated Packings
- Reinforced Crankcase for Increased Load Capacity
- Enlarged Crankcase Increases Oil Capacity for Better Lubrication and Lower Operating Temperatures
- One-Piece Industrial-Grade Oversized Bronze Connecting Rods
- Solid Shaft 24 mm for Belt Drive, Gearbox or Flex Couplers
- Standard versions with p.t.o on right hand side, left side on request.

Specifications

- **Comet Model:** 6307 1100
- **Shaft:** Solid, 24 mm
- **Speed:** 1450 RPM
- **Flow:** 13 L/min - 3.4 GPM
- **Pressure:** 3000 PSI - 207 BAR - 20.7 Mpa
- **Power:** 6.5 HP - 4.9 kW
- **Weight:** 7.9 KG - 17.4 lbs
- **Inlet:** 1/2" BSP Female
- **Outlet:** 3/8" BSP Female
- **Head Material:** Brass
- **Pump Type:** High Temperature



HIGH TEMPERATURE PRESSURE PUMP - **BAR** ZW SERIES - SOLID, 24 MM SHAFT - COMET

