

SKU: 220 ESHR 38/600-2200

Pressure - 8700 psi

Flow - 38 L/min

Speed - 2200 RPM



Features

- Pump body : aluminium alloy
- Symmetric crankcase featuring top and bottom fixing for easy right to left shaft conversion
- Triplex plunger pump in line
- Head: stainless steel
- Camshaft: forged steel
- Splash lubrication
- Shaft support tapered roller bearings oversized for long duration
- Connecting rods: steel with thin-shell bearings
- Guiding piston: stainless steel
- Solid ceramic plungers
- Stainless steel suction/delivery valves
- Seals: high dependability
- Versions in direct drive mount or with side gearbox available in 3 gear ratios and positionable on the right or left of the pump at 0° – 45° – 90° – 135° – 180° from the horizontal plane (see drawing)

Specifications

- **HPP Model** - ESHR 38/600
- **HPP Code** - 6925 0007
- **Speed** - 2200 RPM
- **Flow** - 38 L/min
- **Pressure** - 8700 psi
- **Power** - 61 hp
- **Max Inlet Pressure:** 43.5 psi
- **Oil Capacity:** 5.65 L – 80W 90
- **Oil Capacity with Gearbox:** 7.1 L – 80W 90
- **Weight** - 98 kg

Options

- PULSE system on request



