HIGH PRESSURE TRIPLEX PUMP - LW SERIES - HOLLOW, 28 MM SHAFT -COMET

SKU: 210 LW2520E

9.4 L/min @ 2000 PSI 1450 RPM 3.5 HP, Suits Electrical Engines

Features

- 1. Brass Head
- 2. Forged Bronze Connecting Rods with Lifetime Warranty
- 3. Hardened Stainless Steel Piston Guides
- 4. High Efficiency Stainless Steel Check Valves
- 5. Abrasion Proof, Heat Resistant, Industrial Ceramic Plungers
- 6. High Quality Buna- Textile Double-Sealing V-Packings
- 7. Die-Cast, Anodized Aluminum Crankshaft-Fin Design for Optimal operating Temperature
- 8. High Quality Oversized Ball Bearings
- 9. Optimal Oil Bath for High Speed Operation
- 10. 28mm HOLLOW SHAFT with flange for coupling to electric engines
- 11. Stainless steel head available on request
- 12. Standard versions with p.t.o on right hand side, left side on request.

Specifications

- Comet Model: 6300 1100
- Shaft: Hollow, 28 mm
- Speed: 1450 RPM
- Flow: 9.4 L/min 2.5 GPM
- Pressure: 2000 PSI 138 BAR 13.8 Mpa
- Power: 3.5 HP 2.6 kW
- Weight: 6.5 KG 14.4 lbs
- Inlet: 1/2" BSP Female
- Outlet: 3/8" BSP Female
- Head Material: Brass
- Pump Type: Triplex







