# WARTHOG NOZZLE 5000 PSI @ 21 L/MIN

SKU: 165 Warthog WT 3/8 A

## 76 - 152 mm Pipe Size 3/8" BSPP Inlet 3 x 1/8" NPT Nozzle Ports

#### **Features**

Our smaller WT 3/8 Classic series Warthog models can negotiate elbows and clean-outs commonly found in laterals in homes, buildings, restaurants and other light commercial facilities. This tool is most commonly used on mobile jetters to 5,000 Psi.

Also an excellent choice for cutting roots, clearing ice and removing blockages, the WT-3/8-C is designed specifically to handle 3"-6" lines and clean-outs.

- Controlled rotation Slower dwell time allows jets to penetrate deeper through deposits
- Multiple head options Customize tool for unplugging, descaling or manhole cleaning
- Highest quality jets Hardened stainless steel orifices resist cracking and scratching
- Optional descaling head available
- Go to Nozzle Calculator: http://jetting.stoneagetools.com/#/model/39;f=245

### **Specifications**

Pipe Size: 3-6 in - 76-152 mmPressure: 1,500 - 5,000 PSI

Flow: 20 - 45 L/minFlow Rating: 0.75 Cv

• Pulling Force: 5-20 lbs - 2.3-9 kg - 22-90 N

• Inlet: 3/8" BSPP

Nozzle Ports: 3 x 1/8" NPT
Diameter: 1.9 in - 48 mm
Length: 3.0 in - 76 mm
Weight: 1.2 lbs - 54 kg



#### **Recommended Accessories**

- Warthog WT 3/8 Service Kit(B1) 165 Warthog WT600
- Warthog WT602 Seal Kit(B1) 165 Warthog WT602
- WT-3/8-C Overhaul Kit WT610 165 Warthog WT610

