

SAFETY DATA SHEET

Section 1. Identification

CHS Inc. Transportation Emergency (CHEMTREC) : 1-800-424-9300

P.O. Box 64089 Technical Information 1-651-355-8443 Mail station 525

St. Paul, MN 55164-0089 SDS Information : 1-651-355-8445

Product name : Commercial Tractor Fluid (undyed) SDS no. : 1028-601941

Common name : Tractor Hydraulic Fluid Revision date : 05/04/2018

Chemical name : Lubricating oil. Chemical formula : Mixture

Chemical family : Hydrocarbon.

Relevant identified uses of the substance or mixture and uses advised against

Lubricant.

Section 2. Hazards identification

OSHA/HCS status : While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.

1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This

SDS should be retained and available for employees and other users of this product.

Classification of the substance or

mixture

: Not classified.

GHS label elements

Signal word : No signal word.

Hazard statements : No known significant effects or critical hazards.

Precautionary statements

General : Not applicable.

Prevention : Not applicable.

Response : Not applicable.

Storage : Not applicable.

Disposal : Not applicable.

Hazards not otherwise classified : None known.

Hazardous Material Information System (U.S.A.)

Health: 0 / Flammability: 1 Physical hazards: 0

National Fire Protection Association (U.S.A.)

Health: 0 / Flammability: 1 Instability: 1

Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: Lubricating oil.

Other means of identification : Tractor Hydraulic Fluid

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated heavy paraffinic	≥10 - ≤25	64742-54-7

Any concentration shown as a range is to protect confidentiality.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : If material comes in contact with the eyes, immediately wash the eyes with large amounts of water for 15

minutes, occasionally lifting the lower and upper lids. Get medical attention.

Inhalation : If person breathes in large amounts of material, move the exposed person to fresh air at once. If breathing has

stopped, perform artificial respiration. Keep the person warm and at rest. Get medical attention as soon as

possible.

Skin contact : If the material comes in contact with the skin, wash the contaminated skin with soap and water promptly. If the

material penetrates through clothing, remove the clothing and wash the skin with soap and water promptly. If

irritation persists after washing, get medical attention immediately.

Ingestion : If material has been swallowed, do not induce vomiting. Get medical attention immediately.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following: pain or irritation, watering, redness.

Inhalation : Adverse symptoms may include the following: respiratory tract irritation, coughing.

Skin contact: Adverse symptoms may include the following: irritation, redness.

Ingestion: No known significant effects or critical hazards.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested

or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use water spray to cool fire exposed surfaces and to protect personnel. Foam, dry chemical or

water spray (fog) to extinguish fire.

Unsuitable extinguishing media

Specific hazards arising from the chemical

pecific nazards arising from the chemical

Hazardous thermal decomposition products Special protective actions for fire-fighters

Special protective equipment for fire-fighters

No specific data.

None known.

When fighting fires wear full turnout gear and self contained breathing apparatus. Water may

cause splattering. Material floats on water.

Toxic fumes gases or vapors may evolve on burning.

: Not applicable.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel :

: Keep unnecessary and unprotected personnel from entering. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Methods and materials for containment and cleaning up

Spill

: Contain with dikes or absorbent to prevent migration to sewers/streams. Take up small spill with dry chemical absorbent; large spills may require pump or vacuum prior to absorbent. May require excavation of severely contaminated soil.

Section 7. Handling and storage

Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing.

Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator

when ventilation is inadequate.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.

Conditions for safe storage, including any incompatibilities

: Do not store above the following temperature: 80°C (175°F). Odorous and toxic fumes may form from the decomposition of this product if stored at excessive temperatures for extended periods of time. Store in accordance with local regulations. Do not store at temperatures exceeding 113°F (45°C). Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy paraffinic	OSHA PEL (United States, 6/2016). TWA: 5 mg/m³ 8 hours. ACGIH TLV (United States, 3/2017). TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2016). TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist

Appropriate engineering controls

: Use only with adequate ventilation.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection Skin protection : Recommended: Splash goggles and a face shield, where splash hazard exists.

Hand protection
 Body protection
 Recommended: Long sleeved coveralls.
 Other skin protection
 Recommended: Impervious boots.

Respiratory protection

: If ventilation is inadequate, use a NIOSH-certified respirator with an organic vapor cartridge and P95 particulate

Section 9. Physical and chemical properties

<u>Appearance</u>		Relative density	: 0.88 to 0.89	
Physical state	: Liquid.	Evaporation rate	: <1 (Butyl acetate = 1)	
Color	: Amber.	Solubility	: Insoluble in the following materials: cold water and hot water.	
Odor	: Mild.	Solubility in water	: Insoluble	
Odor threshold	: Not available.	Partition coefficient: n-	: Not available.	
рН	: Not available.	octanol/water		
Melting point	: Not available.	Auto-ignition temperature	: >260°C (>500°F)	
Boiling point	: Not available.	Decomposition temperature	: Not available.	
Flash point	: Closed cup: >165°C (>329°F)	SADT	: Not available.	
Flammability	: Not available.	Viscosity	: Not available.	
Lower and upper	: Not available.	Vapor pressure	: <0.13 kPa (<1 mm Hg) (68°F)	
explosive (flammable) limits		Vapor density	: Not available.	

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition products: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

There is no data available.

Irritation/Corrosion

 Skin
 : Not hazardous (per manufacturer).

 Eyes
 : Not hazardous (per manufacturer).

 Respiratory
 : Not hazardous (per manufacturer).

Sensitization

Skin: Not hazardous (per manufacturer).Respiratory: Not hazardous (per manufacturer).

Mutagenicity

There is no data available.

Carcinogenicity

There is no data available.

Reproductive toxicity

There is no data available.

Teratogenicity

There is no data available.

Specific target organ toxicity (single exposure)

There is no data available.

Specific target organ toxicity (repeated exposure)

There is no data available.

Aspiration hazard

Name	Result	
Distillates (petroleum), hydrotreated heavy paraffinic	ASPIRATION HAZARD - Category 1	

Information on the likely routes of

: Dermal contact. Eye contact. Inhalation. Ingestion.

exposure

Section 12. Ecological information

Toxicity

There is no data available.

Persistence and degradability

There is no data available.

Bioaccumulative potential

There is no data available.

Mobility in soil

Soil/water partition coefficient (Koc) : There is no data available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Section 14. Transport information

DOT IDENTIFICATION NUMBER Not applicable. DOT proper shipping name Not applicable.

DOT Hazard Class(es) Not applicable. PG Not applicable. DOT EMER. RESPONSE GUIDE NO. Not applicable

Section 15. Regulatory information

U.S. Federal regulations : TSCA 4(a) final test rules: 2-Butenedioic acid (E)-, di-C8-18-alkyl esters

TSCA 8(a) PAIR: 2-Butenedioic acid (E)-, di-C8-18-alkyl esters TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Water Act (CWA) 311: Vinyl acetate

Clean Air Act Section 602 Class I Substances : Not listed DEA List I Chemicals (Precursor Chemicals) : Not listed Clean Air Act Section 602 Class II Substances : Not listed DEA List II Chemicals (Essential Chemicals) : Not listed

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs) : Listed

SARA 302/304

Composition/information on ingredients

			SARA 302 TPQ		SARA 304 RQ	
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
Vinyl acetate	≤0.001	Yes.	1000	129	5000	644.8

SARA 304 RQ : 5555555555.6 lbs / 2522222222.2 kg [752882056.5 gal / 2849968612.7 L]

SARA 311/312

Hazard classifications : Not applicable.

Composition/information on ingredients

Name	Classification
Distillates (petroleum), hydrotreated heavy paraffinic	ASPIRATION HAZARD - Category 1

SARA 313 : This product (does/not) contain toxic chemicals subject to the reporting requirements of SARA Section 313 of

the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

Product name	CAS number	%
Zinc compounds	Mixture	0.13 as Zinc

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: Distillates (petroleum), solvent-dewaxed heavy paraffinic; Distillates

(petroleum), hydrotreated heavy paraffinic

New York : None of the components are listed.

New Jersey : The following components are listed: Distillates (petroleum), solvent-dewaxed heavy paraffinic; Distillates

(petroleum), hydrotreated heavy paraffinic

Pennsylvania : None of the components are listed.

California Prop. 65

No products were found.

Section 16. Other information

Revision date : 05/04/2018 Supersedes : 10/28/2015

Revised Section(s) : 1, 3, 8, 11, 15, 16. Prepared by : KMK Regulatory Services Inc.

Notice to reader
THE INFORMATION CONTAINED IN THIS SDS RELATES ONLY TO THE SPECIFIC MATERIAL IDENTIFIED. IT DOES NOT COVER USE OF THAT MATERIAL IN COMBINATION WITH ANY OTHER
MATERIAL OR IN ANY PARTICULAR PROCESS. IN COMPLIANCE WITH 29 C.F.R. 1910.1200(g), CHS HAS PREPARED THIS SDS IN SEGMENTS, WITH THE INTENT THAT THOSE SEGMENTS BE
READ TOGETHER AS A WHOLE WITHOUT TEXTUAL OMISSIONS OR ALTERATIONS. CHS BELIEVES THE INFORMATION CONTAINED HEREIN TO BE ACCURATE, BUT MAKES NO
REPRESENTATION, GUARANTEE, OR WARRANTY, EXPRESS OR IMPLIED, ABOUT THE ACCURACY, RELIABILITY, OR COMPLETENESS OF THE INFORMATION OR ABOUT THE FITNESS OF
CONTENTS HEREIN FOR EITHER GENERAL OR PARTICULAR PURPOSES. PERSONS REVIEWING THIS SDS SHOULD MAKE THEIR OWN DETERMINATION AS TO THE MATERIAL'S
SUITABILITY AND COMPLETENESS FOR USE IN THEIR PARTICULAR APPLICATIONS.