



HOT WATER PRESSURE WASHER

OIL / DIESEL FIRED



Adjustable thermostat
up to 200°F with LED rocker
switch and hour/tach meter

American made
heavy duty 7000 PSI
rupture disk

Heavy-duty **roll-cage powder
coated 1.5" OD** steel tube
frame, with centre balanced
lift hook (above industry standards)

Rigid insulated
combustion chamber

**Stainless-steel coil
skin** provides extra
durability and
resists corrosion
and heat

**12v DC Oil-fired
Beckett burner**
with low voltage
inhibitor, prevents
burner from starting
up if battery voltage
is dropped

Mounting bracket
for truck mounting

13" heavy-duty
flat free tires

Powerase electric
start w/ 18amp charge

triplex direct-drive
general pump carries
a **5-year warranty**

Adjustable pressure
relief valve

12" oil drain hose for
ease of maintenance

**7-gallon, removable,
rust-proof polyethylene
fuel tank** with fuel
gauge in cap

Brake kit assembly

Marine sealed battery
box with 55 AH AGM deep
cycle battery

3/4"HD Threaded
mount axle

360° Hose reel
swivel bracket

FEATURES

- Gun/wand assembly with insulated grip and quick connects
- 50' high pressure hose w/quick connects
- 20% chemical injector assembly with quick connects
- 4 color-coded QC spray nozzles
- 1 color-coded QC chemical nozzle



POWER EASE

DIRECT DRIVE

MODEL	GPM	PSI	CC's	ENGINE	BTU/HR	PUMP MODEL	DRIVE	BURNER FUEL CONS.	UNIT DIMENSIONS	SHIPPING DIMENSIONS	SHIP WT (lbs)
HW4015RA	4	4000	420	POWEREASE	330,000	AR RSV4040	DIRECT	2.21 GPH	47"L x 31"W x 50"H	52"L x 36"W x 55"H	530