

HS SERIES

PRESSURE WASHERS



THE RUGGED SKID FRAME OF THE HS SERIES MAKES IT A GREAT OPTION FOR MOUNTING ON A TRAILER, GIVING YOU THE CAPABILITY TO CLEAN DIRT, OIL AND GRIME LITERALLY ANYWHERE.

HS-4005-OMDK

PUMP

- External bypass system protects from heat build-up
- Factory preset unloader
- Forged brass manifold
- 80-mesh, high-volume, stainless-steel screen inlet water strainer

ENGINE

- Electric start – sealed battery included

FRAME

- Heavy-duty powder coated steel frame

COMPONENTS

- 2900-watt generator
- Heavy-duty dual cogged belt drive system
- No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel)
- 1/2-inch schedule 80-coil with stainless-steel wrap

MISCELLANEOUS

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch steel wire-braided hose (1/2-inch hose on HS-3008 model)
- Adjustable pressure insulated dual lance with trigger gun

LIMITED WARRANTIES

- 3 year coil
- 3 year Honda, Kohler, Kubota and Vanguard engines
- 7 year AR and General pumps

CERTIFICATION

- CSA Certified – US and Canada

GASOLINE MODELS

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	Mi-T-M NO.	ENGINE FUEL TANK CAP.	BURNER FUEL TANK CAP.	BURNER FUEL CONS.	BTU PER HOUR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
HS-3005-OMGV	3000	4.8	480cc Vanguard OHV	General	3-0202	10.0 gallons	10.0 gallons	3.37 gph	471,800	50x34x46in.	816 lb.	710 lb.
HS-3008-1MGK*	3000	7.8	725cc Kohler CH730 OHV	General	3-0301	10.0 gallons	10.0 gallons	3.67 gph	513,800	50x34x46in.	816 lb.	710 lb.
HS-3505-1MGH	3500	4.7	688cc Honda GX630 OHV	General	3-0202	10.0 gallons	10.0 gallons	3.37 gph	471,800	50x34x46in.	854 lb.	750 lb.
HS-3505-1MGK	3500	4.7	674cc Kohler CH640 OHV	General	3-0202	10.0 gallons	10.0 gallons	3.37 gph	471,800	50x34x46in.	854 lb.	750 lb.
HS-3506-1MGH	3500	5.6	688cc Honda GX630 OHV	General	3-0202	10.0 gallons	10.0 gallons	3.37 gph	471,800	50x34x46in.	864 lb.	760 lb.
HS-3506-1MGK	3500	5.6	725cc Kohler CH730 OHV	General	3-0202	10.0 gallons	10.0 gallons	3.37 gph	471,800	50x34x46in.	864 lb.	760 lb.
HS-4004-1MAH*	4000	4.0	688cc Honda GX630 OHV	AR	3-0213	10.0 gallons	10.0 gallons	2.76 gph	386,400	50x34x46in.	854 lb.	750 lb.
HS-4004-1MAK*	4000	4.0	674cc Kohler CH640 OHV	AR	3-0213	10.0 gallons	10.0 gallons	2.76 gph	386,400	50x34x46in.	854 lb.	750 lb.

*Model equipped with trapping unloader, all other models equipped with K7 flow actuated unloader.
 Note: All gasoline models sold in California are required to have the HX-0287 CARB compliant fuel tank.

DIESEL MODELS

MODEL NUMBER	PSI	GPM	HORSEPOWER/ENGINE	PUMP	Mi-T-M NO.	ENGINE FUEL TANK CAP.	BURNER FUEL TANK CAP.	BURNER FUEL CONS.	BTU PER HOUR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
HS-3006-OMDK	3000	5.6	16.8 HP Kubota Z602 OHV	General	3-0202	10.0 gallons	10.0 gallons	3.37 gph	471,800	56.5x34x46in.	940 lb.	836 lb.
HS-3505-OMDK	3500	4.7	16.8 HP Kubota Z602 OHV	General	3-0202	10.0 gallons	10.0 gallons	3.37 gph	471,800	56.5x34x46in.	940 lb.	836 lb.
HS-4005-OMDK*	4000	4.5	16.8 HP Kubota Z602 OHV	General	3-0202	10.0 gallons	10.0 gallons	3.37 gph	471,800	56.5x34x46in.	940 lb.	836 lb.

*Model equipped with trapping unloader, all other models equipped with K7 flow actuated unloader.

HS SERIES



AW-9000-0003 dual-axle trailer shown with HS-4005-1MAH hot water pressure washer and hose reel (available as accessories)

ACCESSORIES AND OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
20-1070A18	Removable painted front panel	All models
20-1366A52	Black powder coated rain cap, octagonal	All models
50-0177	Stack adapter	All models
850-0324	Gasket (for 50-0177)	All models
850-0444	Powder coated skid mounting brackets, set of 4	All models
AW-5740-0000	Wheel kit	All models
AW-6000-1006	Equipment cover	All models
AW-8400-0021	Low pressure detergent injector	All models, except HS-3008, HS-3506 & HS-3006 models
HX-0130	Three-way ball valve	All models
HX-0131	High pressure detergent injector, K7	3000 to 3500-PSI models
HX-0133	Steam combination 250°F, K7	HS-3005 & HS-3505 models
HX-0135	Steam combination 250°F, K7	HS-3506-1MGH
HX-0136	Steam combination 250°F, K7	HS-3006-0MDK
HX-0138*	Steam combination 250°F	HS-3005-0MGV
HX-0139*	Steam combination 250°F	HS-3505 models
HX-0140*	Steam combination 250°F	HS-3506-1MGH

PART NUMBER	DESCRIPTION	FITS MODELS
HX-0141*	Steam combination 250°F	HS-3006-0MDK
HX-0142	Steam combination 250°F	4000-PSI models
HX-0143	Trapping unloader	HS-3006 & HS-3506 models
HX-0144*	Dual gun	HS-3006 & HS-3506 models
HX-0145	Adjustable thermostat, 86°-248°F	All models
HX-0146	Hour meter	All models
HX-0147	Four point lifting capability	All models
HX-0148*	Adjustable detergent valve	All models
HX-0200	Trapping unloader	HS-3005 & HS-3505 models
HX-0202	Dual gun	HS-3008-1MGK
HX-0252	Pressure washer option for PWR-10-0ME1 trailer-mount package	HS-3505-1MGH
HX-0285	30-gallon steel diesel fuel tank	Diesel models
HX-0287	California compliant fuel tank – Replaces the EPA plastic tank with a CARB approved painted steel tank	All models, required on gasoline models sold in California

**Requires trapping unloader.
Note: To order options HX-0138 to HX-0141, HX-0144 or HX-0148 you must order option HX-0143 or HX-0200 (not required for 4000-PSI models, which already come equipped with trapping unloader).*