



Model	iGX700	iGX800
Engine Type	4-stroke 2-cylinder OHV petrol engine horizontal shaft	4-stroke 2-cylinder OHV petrol engine horizontal shaft
Fuel system	Electronic fuel injection	Electronic fuel injection
Cylinder sleeve type	Cast iron sleeve	Cast iron sleeve
Bore x stroke	2 / 78 x 72	2 / 83 x 72
Displacement	688 cm ³	779 cm ³
Compression ratio	9.3	9.1
Net power	16.5 kW (22.1 HP) / 3600 rpm	18.5 kW (24.8 HP) / 3600 rpm
Cont. rated power	11.5 kW (15.4 HP) / 3000 rpm 13.0 kW (17.4 HP) / 3600 rpm	13.3 kW (17.8 HP) / 3000 rpm 15.0 kW (20.1 HP) / 3600 rpm
Max. net torque	48.3 Nm / 4.93 kgfm / 2500 rpm	54.5 Nm / 5.56 kgfm / 2500 rpm
Ignition system	Full-transistor ignition coil	Full-transistor ignition coil
Lubrication	Full-pressure	Full-pressure
Starting system	Electric starter	Electric starter
Fuel cons. at cont. rated power	6.57 L/h - 3600 rpm	6.88 L/h - 3600 rpm
Engine oil capacity	1.7 L	2.1 L
Dimensions (L x W x H)	429 x 483 x 438 mm (T-type)	429 x 492 x 438 mm (T-type)
Dry weight	47.5 kg	48.2 kg

* Subject to changes