
2" KOHLER HIGH PRESSURE FIRE PUMP



SKU:124 HD20101-KEJMP

Max Flow 450 L/min flow rate Max Head 80 m, 7 m Suct. Kohler 10.9 hp diesel engine





KOHLER.

BE 2" Kohler Diesel High Pressure Fire Pump Electric Start

BE "Kohler Diesel" high pressure pumps are the top choice for heavy duty professionals. When you require consistant & dependable performance for hours on end, this is the go-to unit.

These built in Australia units feature a heavy duty cast iron pump end mounted in rugged galvanised with anti vibration mounts and battery pack. Units are powered by Kohler KD15-440, 10.9 hp air cooled diesel engine.

Performance

- 450 L/min. flow rate (max)
- •7 m suction lift (max)
- •80 m total head (max)

Pump Features

- Clean water pump
- 2" BSP suction port
- 2" BSP discharge port
- Cast Iron body & single impeller
- Standard with NBR seals & Ceramic mechanical seal
- •3 way outlet option available part # 125 85.572.135
- Viton seals available upon request

Unit & Frame

Galvanized steel roll frame

Engine

- Kohler KD15-440 10.9 hp diesel engine
- Air cooled direct injection
- Electric start
- •5 L Fuel tank
- •Low vibration & noise
- Kohler 2 year limited warranty

Applications

- Fire fighting, mop up & general fire protection
- High-pressure water transfer
- Spray irrigation
- Diesel fuel transfer with Viton seals fitted
- High-pressure spraying
- Sheep jetting
- Boom spraying
- Stock crate wash down
- Machinery wash down

